



[Home](#) > [Professionals](#) > [Select Region](#) > [All Regions](#) > [Pave Stones](#) > Venetian Stone™ Giant

## Venetian Stone™ Giant



All Regions

### Pallet Specs

|                   |             |
|-------------------|-------------|
| Pallet Weight:    | 3228 lbs.   |
| Sq. Ft. / Pallet: | 120 sq. ft. |
| Product Number:   | 270         |

### Stone Specs

|                  |                  |
|------------------|------------------|
| Length:          | 11 3/4in / 298mm |
| Width:           | 11 3/4in / 298mm |
| Height:          | 2 3/8in / 60mm   |
| Weight / Stone:  | 26.9 lbs         |
| Stones / Pallet: | 120 stones       |
| Stones / Sq Ft:  | 1 stones         |

### Applications

Driveways  
Patio  
Entrance Areas  
Sidewalks  
Terraces  
Garden Pathways  
Pool Decks  
Pedestrian Malls  
Courtyards  
Plazas



## Venetian Stone™ Giant

The Venetian Stone™ product advent is the latest development in enhanced pavements. Its uniquely attractive cleft surface sets it apart from other pavement treatments. This texture resembles old world charm and invokes a traditional convention. The Venetian Stone™ larger scales lends itself to stately residential settings and more expansive commercial applications. Its modular pattern equalizes the scale of any project and is fitting to most any architectural elements.

## Composition & Manufacture

Venetian Stone™ is made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Venetian Stone™ has a compressive strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936.

## Installation

Excavate unsuitable, unstable or unconsolidated subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for base material. Typically the base material is 4 in. to 8 in. (101mm to 202mm) in depth of compacted base for light vehicular and pedestrian traffic or as otherwise directed by Site Engineer/Architect/Landscape Architect. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required. Install Venetian Stone™ with vertical side joints approximately 1/8 in. (3mm) in width. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaged edges. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement. Spread sand to 1/8 in. thickness over entire paving area. Stabilization of jointing sand may be required. Make one more pass with plate compactor to fill joints with sand.

### Product Images

Venetian Stone™ Giant is a trademark of the Pavestone Company. This product may not be available in every market we service.

[Home](#) > [Professionals](#) > [Select Region](#) > [All Regions](#) > [Pave Stones](#) > Venetian Stone™ Large Rectangle

## Venetian Stone™ Large Rectangle



All Regions

### Pallet Specs

|                   |            |
|-------------------|------------|
| Pallet Weight:    | 2680 lbs.  |
| Sq. Ft. / Pallet: | 96 sq. ft. |
| Product Number:   | 269        |

### Stone Specs

|                  |                   |
|------------------|-------------------|
| Length:          | 11 3/4in / 298mm  |
| Width:           | 5 13/16in / 148mm |
| Height:          | 2 3/8in / 60mm    |
| Weight / Stone:  | 13.4 lbs          |
| Stones / Pallet: | 200 stones        |
| Stones / Sq Ft:  | 2.1 stones        |

### Applications

- Driveways
- Patios
- Entrance Areas
- Sidewalks
- Terraces
- Garden Pathways
- Pool Decks
- Pedestrian Malls
- Courtyards
- Plazas



## Venetian Stone™ Large Rectangle

The Venetian Stone™ product advent is the latest development in enhanced pavements. Its uniquely attractive cleft surface sets it apart from other pavement treatments. This texture resembles old world charm and invokes a traditional convention. The Venetian Stone™ larger scales lends itself to stately residential settings and more expansive commercial applications. Its modular pattern equalizes the scale of any project and is fitting to most any architectural elements.

## Composition & Manufacture



[Home](#)  
 [Estimators](#)  
 [Technical](#)  
 [About Us](#)  
 [Contact Us](#)  
[Consumers](#)

[Home](#) > [Professionals](#) > [Select Region](#) > [All Regions](#) > [Pave Stones](#) > Venetian Stone™ 2Pc Combo...

Venetian Stone™ 2Pc Combo (60mm)



All Regions

Pallet Specs

Pallet Weight: 2690 lbs.  
 Sq. Ft. / Pallet: 95 sq. ft.  
 Product Number: 267

Med. Rec 8 3/4 x 5 13/16 x 2 3/8

Length: 8 3/4in / 223mm  
 Width: 5 13/16in / 148mm  
 Height: 2 3/8in / 60mm  
 Weight / Stone: 10.1 lbs  
 Stones / Pallet: 200 stones

Square 5 13/16 x 5 13/16 x 2 3/8

Length: 5 13/16in / 148mm  
 Width: 5 13/16in / 148mm  
 Height: 2 3/8in / 60mm  
 Weight / Stone: 6.7 lbs  
 Stones / Pallet: 100 stones

Applications

- Driveways
- Patios
- Entrance Areas
- Sidewalks
- Terraces
- Garden Pathways
- Pool Decks
- Pedestrian Malls
- Courtyards
- Plazas



### Venetian Stone™ 2Pc Combo (60mm)

The Venetian Stone™ product advent is the latest development in enhanced pavements. Its uniquely attractive cleft surface sets it apart from other pavement treatments. This texture resembles old world charm and invokes a traditional convention. The Venetian Stone™ larger scales lends itself to stately residential settings and more expansive commercial applications. Its modular pattern equalizes the scale of any project and is fitting to most any architectural elements.

### Composition & Manufacture

Venetian Stone™ is made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Venetian Stone™ has a compressive strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936.

## Installation

Excavate unsuitable, unstable or unconsolidated subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for base material. Typically the base material is 4 in. to 8 in. (101mm to 202mm) in depth of compacted base for light vehicular and pedestrian traffic or as otherwise directed by Site Engineer/Architect/Landscape Architect. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required. Install Venetian Stone™ with vertical side joints approximately 1/8 in. (3mm) in width. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaged edges. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement. Spread sand to 1/8 in. thickness over entire paving area. Stabilization of jointing sand may be required. Make one more pass with plate compactor to fill joints with sand.

## Product Images

Venetian Stone™ 2Pc Combo (60mm) is a trademark of the Pavestone Company. This product may not be available in every market we service.

[Privacy Policy](#) | [Pavestone Sitemap](#)



[Login](#) | [Intranet](#)

© Copyright 2011 Pavestone Company - All Rights Reserved